



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure GK16TIWSZ



Selected product

- Article no.: 3108860105
- EAN code: 7630029425299
- Type: GK16TIWSZ
- Product category: Hob
- Standard width: 40 cm
- Front design: BlackDesign
- Frame: DualDesign



Details GK16TIWS

Design

- Type: GK16TIWSZ
- Product category: Hob
- Standard width: 40 cm
- Front design: BlackDesign
- Frame: DualDesign

Dimensions

- Cut-out radius: 5 mm
- Appliance height: 128.5 mm
- Appliance width: 384 mm
- Appliance depth: 501 mm
- Appliance corner radius: 1.5 mm
- Support size width: 373 mm
- Max. support size width: 373 mm
- Support size depth: 490 mm
- Max. support size depth: 490 mm
- Installation height when flush-fitted: 128.5 mm
- Installation height when surface-mounted: 124.5 mm
- Cut-out width when flush-mounted: 390 mm
- Cut-out width when surface-mounted: 373 mm
- Max. cut-out width when surface-mounted: 373 mm
- Cut-out depth when flush-mounted: 507 mm
- Cut-out depth when surface-mounted: 490 mm
- Max. cut-out depth when surface-mounted: 490 mm
- Empty weight: 9 kg
- Cooking zone 1 position: central
- Cooking zone 1 dimensions: 30 cm (cuvette)

Display and operation

- Display: Digital display
- Controls: Single slider
- Slider control
- Operating time
- Languages in display: -
- Button sound (on/off)

Energy

- Consumption when off: 0.0 W
- Cooking zone 1 max. power: 3000 W
- Type of connection (1): 220-240 V~
- Frequency (1): 50-60 Hz
- Connected loads (1): 3 kW
- Fuse protection (1): 16 A
- Plug type: cable

Hob features

- Hob category: Induction
- Operating time with shut-down function
- Residual heat indicator
- Timer
- Restore function
- Cooking zones: 1
- Power levels: 9
- EcoStandby
- Heating technology: induction cooking zones

Functions

- Warming function
- Childproof lock
- Powerplus
- Safety package
- Pan detection: No
- Pause button
- Cleaning lock
- Melt function
- Simmer function

Additional data

- Feature level: 4

Service and interfaces

- Warranty: 2 years